# DDI602-F2

**Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)**



# DDI602-F2

## Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)

## Tekniske specifikationer

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Vægmontering |
| Anti masking | No |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Microwave frequency (nom.) | 10.587 GHz |
| Undercrawl protection | No |
| Alarm time | 5 s |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Multiple EOL values |

### Physical

| | |
|---|---|
| Colour | Sølv |
| Material | Høj slag ABS plast med HDPE dæksel, UV stabiliseret |
| Mounting height | 3 to 6 m |

### Environmental

| | |
|---|---|
| Environment | Udendørs |

### Regulatory

| | |
|---|---|
| Certification | INCERT |

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57