# BS121N

## Battery, 12 V, 1.2 Ah, Interlogix

### Product overview

Sealed lead acid battery 12 V, 1.2 Ah with Fast-on 4.8 mm terminal type.




### Details

- Maintenance free 12 VDC
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS121N

## Battery, 12 V, 1.2 Ah, Interlogix

## Technical specifications

### General

| | |
|---|---|
| Product type | Batteripakke, NiCd batteri, Forseglet blybatteri |

### Electrical Characteristics

| | |
|---|---|
| Nominal voltage | 12 V |
| Nominal capacity | 1.2 Ah |
| Internal approx. resistance | 75 mOhm |

### Charge / discharge

| | |
|---|---|
| Max. charge voltage | 13.8 VDC at +20°C |
| Max. charge current | 0.36 A |
| Max. discharge current | 6 A |

### Temperature

| | |
|---|---|
| Charging temperature | 0 to +40°C |
| Discharging temperature | -15 to +50°C |

### Physical

| | |
|---|---|
| Physical dimensions | 97 x 43 x 53 mm |
| Net weight | 0.596 kg |
| Shipping weight | 0.596 kg |
| Material | Metal |
| Terminal type | Fast-on 4.8 mm |

### Environmental

| | |
|---|---|
| Fire retardant | No |
| Operating temperature | 0 to +40°C |
| Storage temperature | -15 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS 2, WEEE |
| Certification | VdS |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:33