DT713-7

Rivelatore termico/termovelocimetrico convenzionale serie 700, 70°C Class B



DT713-7

Rivelatore termico/termovelocimetrico convenzionale serie 700, 70°C Class B

Specifiche tecniche

Electrical

Power supply type	Zone powered

Detection

Alarm temperature (typical)	+70°C ± 1.5°C

Physical

Colour	Cloud white (RAL 9001)
Mounting type	Ceiling mount
Material (body)	Plastic

Environmental

Vandal proof	No
Application temperature (maximum)	+65°C
Application temperature (typical)	+40°C
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Prodotti compatibili

Categoria	Riferimento	Descrizione
Detection device	DB702	Base con 6 terminali per serie 700.
Notification device	AI672	Ripetitore luminoso di allarme a led.
Notification device	AI673	Ripetitore luminoso di allarme a led con buzzer.

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57