ES3402-16P-2S

Switch económico de 16 portas Gigabit com gestão básica e PoE, com 2 ligações de uplink SFP de 1000 Mbps

Overview

The IFS ES3402 series of Economy PoE+ switches are designed to be a cost-effective network switch solution for small to mid sized IP camera surveillance systems. The switches are available in 8 or 16-port Gigabit PoE+ configurations with both versions having two additional 1000BASE-FX/SX/LX SFP ports. Allowing for basic management and PoE functionality, the switches meet the basic need of providing Gigabit Ethernet ports for IP cameras and NVR/Server connections.

Robust layer 2 features

The ES3402-16P-2S can be programmed for basic switch management functions such as port speed configuration, port aggregation, VLAN, bandwidth control and IGMP snooping. This switch provides 802.1Q tagged VLAN Protocol functions. By supporting port aggregation, the ES3402-16P-2S allows the operation of a high-speed trunk combined with multiple ports, and supports fail-over as well. Also, the Layer 2 protocol included to help discover basic information about neighboring devices on the local broadcast domain .

PoE usage monitor and power control

Through the power usage chart in the web management interface, the ES3402-16P-2S empowers administrators to real-time monitor the power usage status of connected PDs (Powered Devices). This capability significantly improves facility management efficiency. Additionally, the switch allows for timely activation or deactivation of PoE ports, providing the ability to power off or reboot connected PDs as needed. The PoE schedule function helps you to enable or disable PoE power feeding for each PoE port during specified time intervals and it is a powerful function to help SMBs or enterprises save power and money. It also increases security by powering off PDs that should not be in use during non-business hours.

Flexibility and long-distance extension solution

The two mini-GBIC slots built in the ES3402-16P-2S support SFP auto-detection and dual speed as it features 100BASE-FX and 1000BASE-SX/LX SFP (Small Form-factor Pluggable) fiber transceivers to uplink to backbone switch and monitoring center in long distance. The distance can be extended from 550 meters to 2 kilometers (multi-mode fiber) and up to above 10/20/30/40/50/70/120 kilometers (single-mode fiber or WDM fiber). They are well suited for applications within the enterprise data centers and distributions.



Detalhes

- 8 portas Gigabit Ethernet de 10/100/1000 Mbps com PoE+ 802.3at
- 2 interfaces SFP Gigabit compatíveis com transceptores de fibra SFP 100BASE-FX e 1000BASE-SX/LX
- Gestão simples através da Web
- Verificação de "PD Alive", prioridade PoE, limite de potência PoE, monitorização da utilização de PoE
- Calendário de PoE para poupança de energia
- Funcionalidades robustas de "Layer" 2
- IGMP snooping para um melhor controlo dos fluxos de multicast
- Espelhamento de portas para monitorizar o tráfego de entrada ou saída numa determinada porta (muitos para um)
- Potência PoE total até 240 W

ES3402-16P-2S

Switch económico de 16 portas Gigabit com gestão básica e PoE, com 2 ligações de uplink SFP de 1000 Mbps

Especificações técnicas

General

Storm control	Broadcast
Security	MAC-Adressbindung, TCP / UDP-Filterung
DHCP snooping	No
Fan	2
System LED	PWR (Green)
Port LEDs	LNK/ACT (Green), PoE-in-use (Amber)
Flash memory	16 Mbytes
Reset button	< 10 sec: System reboot, > 10 sec: Factory default
Security functions	Port isolation, DHCP Snooping

Category

Category	Gewerblich
Management	Web Smart
Managed	Yes (Layer 2 - Limited)
PoE	Yes

Physical ports

No. of ports	16
Port type	10/100/1000BASE-T
Speed	Gigabit
PoE/PoE+	16 ports with 802.3af/802.3at PoE+
Fiber port	2
Supported SFPs	S2x und S3x Serie
SFP speed	100/1000
PoE power output	32W (max.)
Power pin assignment	1/2(+), 3/6(-)
PoE power supply type	End-span
PoE standard	IEEE 802.3at PoE+ PSE

Switch Performance

Switch fabric	36 Gbps/non-blocking
Throughput (Mpps)	26.78
Mac table	8 K
Jumbo frame support	10 K

Electrical

PoE power budget	240 W max.
Redundant power	No
Power supply type	100 til 240 VAC
Power consumption	7.1 watts / 24.2BTU (System) 283 watts / 965BTU (System+PoE)
ESD protection	Contact ±6KV , Air ±8KV
Surge protection	Differential mode ±2KV , Common mode ±4KV

Physical

Physical dimensions	440 x 207 x 44 mm
Net weight	2343 g
Colour	Sort
Material	Metal
Mounting type	Baseret på skrivebord, Montering på stativ
Stackable	No

Environmental

Operating temperature	0 a +50°C
Storage temperature	-10 a +70°C
Relative humidity	5 to 95% sem condensação

Regulatory

Compliancy	CE, REACH, RoHS, UKCA
Standards	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3z Gigabit SX/LX IEEE 802.3ab Gigabit 1000Base-T IEEE 802.3x Flow Control and back pressure IEEE 802.1p Class of Service IEEE 802.1Q VLAN Tagging IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet PLUS RFC 783 TFTP RFC 791 IP RFC 792 ICMP RFC 2068 HTTP RFC 1112 IGMP v1 RFC 2236 IGMP v2

Switch performance


Switch architecture	Store-and-forward
Shared data buffer	4.1 MB
Flow control	Back pressure for half duplex. IEEE 802.3x pause frame for full duplex.

Layer 2 Functions

Port configuration	EEE Green energy savings disable/enable, Port disable/enable/reboot, Flow control disable/enable, Bandwidth control on each port, Port loopback protection
Port status	Display each port’s speed duplex mode, Display link status, Display flow control status, Display auto negotiation status, Display Green energy saving status
Port mirroring	In / Out / All, Many-to-1 monitor
VLAN	802.1Q tagged VLAN, up to 16 VLAN groups
Bandwidth control	TX/RX/Both
Link aggregation	Static trunk supporting 8 groups with 8 ports per trunk group
QoS	8 priority queues on all switch ports. Supports strict priority and Weighted Round Robin (WRR) CoS policies. Traffic classification: IEEE 802.1p CoS/ToS, IPv4 DSCP, Port-based WRR
Multicast	IPv4 IGMP v1/v2 snooping, Up to 256

ES3402-16P-2S

Switch económico de 16 portas Gigabit com gestão básica e PoE, com 2 ligações de uplink SFP de 1000 Mbps



Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 20:20