IO950ND

Modul til 950 serien. I/O enhed (SA4700-302)

General

IO950ND is the new DIN-Rail input/output unit which provides supervision of one or more normally open contacts connected to a single pair of cables and a set of changeover relay output contacts.

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Detaljer

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Supervise one or more NO switches on a single cable pair
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO950ND

Modul til 950 serien. I/O enhed (SA4700-302)

Tekniske specifikationer

Electrical

Operating voltage	17 to 35 VDC

Physical

Physical dimensions	102 x 33 x 33 mm
Net weight	49 g

Environmental

Operating temperature	-40 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor

Regulatory

Certification	CPR, EN54-17, EN54-18

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57