ACI420-PIN

OSDP reader with PIN keypad, slim design, Mifare Desfire EV1/2/3, CSN & Bluetooth

Product Overview

The ACI42x range of readers provides an attractive reader in slim line or standard design supporting cards with secure Mifare Desfire EV1/EV2/EV3 security. In addition the reader provides for onboard Bluetooth (BLE) support. The ACI42x-PIN variants include a PIN keypad.

Secure readers

The ACI42x range supports security from the card up to the controller when the controller supports the security features of the OSDP V2.17 standard and the Mifare Desfire EV1/EV2/EV3 cards are encrypted.



Einzelheiten

- Secure OSDP Mifare Desfire EV1/EV2 reader with PIN
- Supports Mifare Desfire EV1/EV2 custom cards and CSN, as well as other Mifare CSN cards
- Address and other settings through configuration cards
- Robust molded plastic housing in slim design
- Indoor or outdoor mounting
- Request to exit input and one output
- Bluetooth BLE onboard
- Supported on CDC4 range of Door/Lift controllers

ACI420-PIN

OSDP reader with PIN keypad, slim design, Mifare Desfire EV1/2/3, CSN & Bluetooth

Technische Spezifikationen

System

Reading distance	up to 5 cm depending on technology used and environment
Max. reader distance to panel	1 km from control panel
CSN (Card Serial Number)	Yes
Custom data model	Yes
Supported card types	Mifare Classic 7 Byte UID, MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® Plus UID, NFC (UID)
Addressing type	Kartenadressierung
No. of LEDs	3 x multi-color

Technology

Reader type	Smartcard
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (benutzerdefinierte Daten), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Benutzerdefinierte Daten), MIFARE Plus (CSN), NFC (CSN)
Supported technology 2.4 GHz	Bluetooth
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Byte (nicht eindeutig), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70)

Interface & connections

Interface	OSDP V2 Sicherer Kanal
Connector type	Zopf
Pigtail length	3 m

Inputs/outputs

Inputs	Aufforderung zum Beenden
Outputs	1 Open Collector (50 mA)

Tamper type

Opening tamper	Yes

Operation

PIN keypad	Yes
PIN length	Depending on controller

Electrical

Operating voltage	10 - 30 VDC
Current consumption	50 mA @ 13.8 VDC normal 120 mA @ 13.8VDC max

Physical

Physical dimensions	148 x 45 x 26 mm
Colour	Schwarz
Material	Plastik
Form factor	Slimline
Mounting Type	Oberflächenmontage

Environmental

Operating temperature	−30 to +55°C
Relative humidity	max 95% noncondensing
Environment	Drinnen, Draussen
IP rating	IP 67 IK 09

Regulatory

Compliancy	CE
Certification	CE

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.