SC-13-1100-0001-99

SmartCell 230VAC intelligentes drahtloses MG-Modul (iWZM)

Wireless Zone Monitor overview

The Wireless Zone Monitor (WZM) has been designed with flexibility in mind, allowing connection to both conventional and addressable fire alarm systems. Supporting up to 16 SmartCell wireless fire devices, communication between devices and the WZM is bidirectional and operates in the European harmonised 868 MHz frequency band.



Einzelheiten

- Drahtlose Gerätekommunikation
- Schnell und einfach zu installieren
- Kompaktes Gehäuse
- 80-Zeichen-Anzeige
- Auch als 24 VDC-Version erhältlich

SC-13-1100-0001-99

SmartCell 230VAC intelligentes drahtloses MG-Modul (iWZM)

Technische Spezifikationen

Electrical

Power supply type	230 VAC
Operating voltage	220 bis 240 VAC, 50 Hz, 0.3 A
Current consumption	5 mA (PSU), plus 100 mA vom WZM

Input

Input quantity	2
Input type and rating	Widerstandsüberwachte Eingänge

Output

Output quantity	2
Output type and rating	1x Feuer & 1 x Störung, Nennspannung 30 V @ 1 A

Physical

Physical dimensions	275 x 220 x 80 mm (B x H x T)
Net weight	1.55 kg
Colour	White
Mounting type	Surface mount
Cable entries	4 x 100 mm (Boden) / 4 x 100 mm (Rückseite)
Batteries	6 V, 4 Ah

Environmental

Operating temperature	-5 bis +45°C
Storage temperature	0 bis +30°C
Relative humidity	95% nicht kondensierend max.
Environment	Indoor
IP rating	IP30

Regulatory

Compliancy	CE
Certification	CPR
Standards	EN54-13 EN54-18 EN54-25

Wireless signalling

Operating frequency	868 to 870 MHz
Output transmitter	14 dBm max. / 25 mW

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.