ADE88-0200

AlarmLine II Digital EN LHD cable 88°C, 200 m

General

The ADE88-0200 is a Digital Linear Heat Detection (LHD) cable with a 88°C fixed temperature activation rating. The ADE range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The ADE range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable is used in combination with the controller and end-of-line (EOL) unit, and can connected to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit to signal an alarm condition.

Alarm location

The control unit can identify along the length of the sensor cable where an alarm condition has occurred. The alarm location is then indicated on the display of the controller. Both zone are displayed at the same time.

Cable fixings for all applications

A range of 'edge' ,'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Details

- EN54-28:2016 approved
- Low-Smoke Zero Halogen
- Up to 1000 m
- Detection along total cable length
- Flame retardant
- Oil resistant
- UV Stable
- Simple low maintenance installation
- RoHS compliant

ADE88-0200

AlarmLine II Digital EN LHD cable 88°C, 200 m

Technical specifications

Electrical

Operating voltage	0 to 49 VAC, 0 to 74 VDC
No. of cable cores	2

Detection

Alarm temperature (typical)	+78°C

Conductor

Resistance	2.5 ohm per m
Capacitance	<100 pF per m
Inductance	<3.2 uH per m

Physical

Physical dimensions	Diameter 5.72 mm +/- 0.12 mm (0.225” +/- 0.0005”)
Colour	Red
Mounting type	Cable mount

Environmental

Operating temperature	-40 to +65°C (Ambient)
Relative humidity	0 to 98% noncondensing

Regulatory

Certification	CE, EN54-28

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 10 September 2026 - 12:55