NC-MC-0-Y

Intelligent conventional recess mount manual call point, 0 Ω (yellow)

General

The NC-MC-0-Y is a yellow manual call point for recess mount applications on most industry standard, high quality wall boxes. For surface mount applications an optional, colour matched back box is available.

The call point offers one normally open contact in series with a 0 Ω resitor, as well as a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a EN54 style resettable element, pluggable connectors for both contacts, a handy wire bridge to help with cable continuity testing, as well as a test key that doubles up as a service tool for disassembly of the device.

Installation

Installation time and installation flexibility are of paramount importance. The KGS MCP range directly meets these needs by providing features designed specifically for this. Pluggable terminal blocks facilitate the pre-connection of all cables. This terminal block is then simply connected to the MCP. Should continuity testing be needed, the handy wire bridge fits neatly into the terminal block in place of the MCP without having to disconnect any cables.

For service and maintenance no additional tools other than the test key is needed. With easy front access in all installations and even with the protection cover fitted, the test key is also used to remove the front cover of the unit should a frangible element need to be replaced.

Options

Both break glass (frangible elements) and re-settable operating elements may be used. The MCP can be configured as either a break glass or re-settable unit by simply changing from one element to another. Other than the optional frangible element, no additional parts are required. Other parts and accessories include colour matched surface mount boxes, recess mount adapters, trim skirts, flip covers, metal test keys and replacement parts.

This range of manual call points is available in various colours with various trigger resistor options to suit most applications. In addition various function markings are available including regional language variants.



Details

- Specifically designed for emergency system control
- Alarm indication by alarm flag
- Enhanced aesthetics with location for custom functional marking
- Resettable and also usable with an optional frangible element
- Easy to install (plug and play)
- Various surface and recess mounting options available for installation flexibility
- Protection hinged cover with anti-tamper facilities available for avoiding accidental activation
- Backward compatible to any conventional system
- Key test facility from the front of the unit for easy access, even when a protection cover is fitted
- Easy service and maintenance with test key disassembly and pluggable connectors

NC-MC-0-Y

Intelligent conventional recess mount manual call point, 0 Ω (yellow)

Technical specifications

General

Status indication	Alarm flag
Compatibility	Conventional alarm systems
Connectivity	Hardwired contacts

Electrical

Power supply type	VDC
Operating voltage	10 to 24 VDC
Current consumption	0 mA (Standby)
Cable specification	0.404 to 2.05 mm (0.13 to 3.31 mm²)
No. of cable cores	2
Terminals	7

Detection

Detection principle	Manual activation
Monitoring	Activated, Off
Coverage area	Region specific
Zone length	<2 km, CIE specific
Response time	< 3 s
Installation height	Determined by local regulation

Output

Output quantity	2
Output type and rating	1 x NO (1 A @ 24 VDC), 1 x change over relay (1 A @ 24 VDC)

Physical

Physical dimensions	87 x 87 x 26 mm (W x H x D)
Net weight	101 g
Colour	Yellow (RAL 1003)
Mounting type	Back box, Wall mount
Material (body)	Flame retardent ABS
Functional marking	None

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-25 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP41

Regulatory


Compliancy	CE, REACH, RoHS 3, WEEE

SKU info

Product series (all languages)	NC-Series

Compatible products

Category	Reference	Description
Detection device	N-MC-AFM-Y	Intelligent MCP accessory - flush mount adaptor - yellow
Detection device	N-MC-BB-Y	MCP accessory, intelligent manual call point back box, yellow
Detection device	N-MC-FC	MCP accessory, intelligent Manual Call Point flip cover
Detection device	N-MC-FE	MCP accessory, intelligent manual call point frangible element



KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 March 2026 - 14:57