W72360-N

SBQ, active IR quad beams, 100 m

Product overview

The new SBQ active infrared beams serie includes quadruple beams, which generate an alarm when 2 beams are interrupted.



Details

- For indooor and outdoor protection
- Easy to install and flexible
- Contains a high power source the beams provide a better detection range and minimum signal loss
- False alarms are reduced as simutaneous interuption of beams is required for alarm condition to occur
- Can be used in range of security applications, mounted on walls, poles or in columns

W72360-N

SBQ, active IR quad beams, 100 m

Technical specifications

General

Category	Active Infrared Beams
Product type	Active Infrared Beam
Infrared system	SBT 100F

Detection

Range	100 m
Alarm response time	50 to 700 ms
Channels	4 channels, CH1 to CH4
Horizontal optical axis adjustment	180° (+/-90°)
Vertical optical axis adjustment	24° (+/-12°)

Inputs/outputs

Alarm output	Form C (NO/NC changeable)

Electrical

Power supply type	12 to 48 VDC
Current consumption	105 mA

Physical

Physical dimensions	353 x 99 x 104 mm
Net weight	1970 g
Colour	Black
Material	ABS, PVC

Environmental

Operating temperature	-25 to +55°C
Environment	Indoor, Outdoor

Regulatory

Compliancy	CE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:33