AS508

Outdoor siren with single amber beacon and inner metal shield



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Metal Inner cover
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Fully compliant with CE, BS and IS requirements
- Self detection of cable cutting or tampering
- Installer Friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS508

Outdoor siren with single amber beacon and inner metal shield

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	114 dB at 1 m (typical)

Flash specifications

Flash frequency	50 to 60 flashes/min

Electrical

Operating voltage	10 to 14.5 VDC
Current consumption	350 mA 40 mA (standby, with NiCd battery) 20 mA (standby, without battery)

Physical

Physical dimensions	210 x 300 x 55 mm
Net weight	1235 g
Material	ABS
Material	ABS (3 mm)

Environmental

Operating temperature	-25 to 55°C
IP rating	IP54

Sounder

	Double piezo

PCB protection

	Fully potted

Tamper & pry-off

	Yes

Frequency

	0.5 to 3 kHz

Cut-off timer

	3, 5, 10, 20 min

Comfort LED

	Yes

Low voltage detection

	Yes

Metal inner cover

	Included

Optional self-activating battery

	10.8 V / 280 mAh

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 May 2026 - 17:12