# ATSX700-PSU

**Replacement power supply (PSU) for Axon panels (ATS1700 and ATS3700)**



## Details

- PSU only (no cables, no mounting brackets etc)
- Mains present indication on PSU

# ATSX700-PSU

## Replacement power supply (PSU) for Axon panels (ATS1700 and ATS3700)

## Technical specifications

### Electrical

| | |
|---|---|
| Mains input | 100-240 VAC<br>50Hz/60Hz |

### Output

| | |
|---|---|
| Power output voltage | 24 VDC |

### Physical

| | |
|---|---|
| Physical dimensions | 99 x 97 x 30 mm (W x H x D) |
| Material | Metal |
| Form factor | Steel cabinet |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Operating temperature | -30 to +70°C |
| Relative humidity | 95% |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS 2, UKCA |

### Load output

| | |
|---|---|
| | 24V, 3.2A |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Control Panel | ATS1700-MBC | Always On. Always Aware.<br>Everon 1700 PCB replacement board |
| Control Panel | ATS1700-MM | Always On. Always Aware.<br>Everon 1700 security panel, IP-onboard, EN grade 3, WebApp, 8 onboard zones max 48 zones, 4 areas, medium metal housing |
| Control Panel | ATS3700-MBC | Always On. Always Aware.<br>Everon 3700 PCB replacement board |
| Control Panel | ATS3700-MM | Always On. Always Aware.<br>Everon 3700 security panel, IP-onboard, EN grade 3, WebApp, 16 onboard zones max 256 zones, 16 areas, medium metal housing |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:25