DDV1016-N

Detector de movimiento PIR/MW, 9 cortinas de 16m, Vector Dual, Pyro Digital, Algoritmo Neuronal

Patented technologies: range gated radar and neural algorithm

Motion sensors of the DDV1016 Series incorporate a KSG Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.Motion sensors of the DDV1016 Series incorporate a KSG Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed. The radar operates on 5.8GHz frequency.

The DDV1016-N motion sensor incorporates a new digital pyro and a brand new neural algorithm to filter out unwanted alarms.
Thanks to these two technologies, a better quality of signals is generated.
The advanced processing combined with a better detection performance result in an extreme low rate of unwanted alarms.

PIR technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.
Using a four element pyro, so generating 4 volumetric curtains for each of the 9 curtain sets, in combination with our VE-techniques allowed us to create a 16m dual tech motion sensor in a rather small housing.

Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.
But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

Ease and flexibility of installation



Detalles

- Tecnología patentada de Radar de alcance controlado seleccionable para definir claramente el límite de la detección
- Tecnología PIR con óptica de espejo de cortinas patentada
- Decisión de alarma inteligente basada en la clasificación de la señal de la alarma de PIR y de radar
- Autodiagnóstico contínuo automático en todas las tecnologías
- Modo ecológico: opción para desconectar la tecnología de radar cuando el sistema de seguridad no está armado
- Cumplimiento de varias normativas de seguridad, incluídas EN Grado II
- Algoritmo patentado para mejorar la inmunidad a falsas alarmas
- Incorpora un nuevo sensor piroelectrico digital que detecta las fluctuaciones de temperatura con gran precisión
- Incorpora un nuevo algoritmo neuronal para filtrar las alarmas no deseadas

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

Other members of the family

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

Neural network-based technology algorithm

Aritech has developed an improved algorithm based on cutting edge neural network-based technology to improve the detection performance and reduce false alarms triggered by external sources. Neural networks are trained to extract complex image features effectively; it allows the detection of slow motion even further apart from the detector.
This algorithm has the aim to improve even further the immunity to false alarms, which is a key concern for major applications of sensors in commercial settings.

DDV1016-N

Detector de movimiento PIR/MW, 9 cortinas de 16m, Vector Dual, Pyro Digital, Algoritmo Neuronal

Especificaciones técnicas

General

Technology	Dual
Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No
Pry-off tamper kit	ST400 (optional)
Detector start-up time	60 s

Detection

Max. detection range	16 m
Detection range selection	4, 6, 9, a 12 m seleccionable por microswitch
No. of curtains	9
Coverage (field of view)	78°
Microwave frequency (nom.)	5.8 GHz
Max. microwave output (at 1m)	0.003 µW/cm²
Undercrawl protection	Yes
Target speed range	0.2 a 3.0 m/s
Alarm memory	Yes
Alarm time	3 s
Peak-to-peak ripple immunity	2 V (a 12 VDC)

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Alarm relay characteristic	NC, 80 mA 30 VDC, Form A
Tamper relay characteristic	NC, 80 mA 30 VDC, Form A
Anti mask relay characteristic	NC, 80 mA 30 VDC, Form A
Relay configuration	Multiple EOL values
Remote control lines	Day/Night, Walk test

Electrical

Power supply value	9 a 15 VDC (12 V nominal)
Current consumption	5 a 16 mA (8 mA nominal)

Physical

Physical dimensions	126 x 63 x 50 mm
Net weight	120 g
Colour	White
Mounting height	1.8 to 3 m

Environmental

Operating temperature	-10 a +55°C
Relative humidity	95% max. sin condensación
Environment	Indoor
IP rating	IP30 IK04

Regulatory

EN50131 grade	Grade 2
Compliancy	CE
Certification	INCERT, NFA2P, VdS



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57