# BS131N

**Battery, 12 V, 18 Ah**



# BS131N

## Battery, 12 V, 18 Ah

## Spécifications techniques

### General

| | |
|---|---|
| Product type | Sealed lead acid battery |

### Electrical Characteristics

| | |
|---|---|
| Nominal voltage | 12 V |
| Nominal capacity | 18 Ah |
| Internal approx. resistance | 10 mOhm |

### Charge / discharge

| | |
|---|---|
| Max. charge voltage | 13.8 VDC at +20°C |
| Max. charge current | 5.4 A |
| Max. discharge current | 90 A |

### Temperature

| | |
|---|---|
| Charging temperature | 0 to +40°C |
| Discharging temperature | -15 to +50°C |

### Physical

| | |
|---|---|
| Material | ABS |
| Terminal type | MS bolt & nuts |

### Environmental

| | |
|---|---|
| Fire retardant | No |
| Storage temperature | -15 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS 2, WEEE |
| Certification | VdS |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57