FE550

Ventouse de maintien 40Kg, pour porte coupe feu, boitier métallique

General

The FE550 is a VDS approved door holder in a reinforced plastic box.

A magnet for all occasions

These door holding magnets are the result of years of specialised development. Rated at just 1.5 W @ 24VDC, these powerful magnets pack a holding power of 490 N. All magnets have a spring-loaded pin to ensure ejection against remnant magnetism.

Application friendly

The reinforced plastic box model offers a cost effective solution without sacrificing performance. The FE550 is supplied without a keeper plate. This may be ordered separately depending on the application.

Installer friendly

For practical ease of installation, all units are complete with electrical termination. Protection diodes prevent electromagnetic pulses, and reverse polarity protection speeds up installation. The boxes are predrilled in a practical, standard format for rapid mounting.

Approvals

All models are VdS approved. (Refer to the device specification)



Détails

- Complete range for wall and surface mount
- Low power - 1.5 W
- 490 N holding power on VDS coils
- 100% duty cycle
- Anti-remnant ejector
- Protection diode and reverse polarity protection
- Release button
- Vds approved (see specification)

FE550

Ventouse de maintien 40Kg, pour porte coupe feu, boitier métallique

Spécifications techniques

General

Release button	Yes

Electrical

Power supply type	24 VDC

Produits compatibles

Catégorie	Référence	Description
Door Holders	FE527	Platine d'ancrage standard pour les aimants de la série FE500
Door Holders	FE529	Swivel Anchorplate for FE500 Series Doormagnets

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57