6515PI

Sensore PIR 15m Comfort line, pet friendly

Tailored to each security need

A complete sensor line offering the comfort to choose the right solution tailored to the risk level and environment. The 6515 model provides standard Passive Infrared (PIR) detection while the 6515PI variant introduces pet immunity, reducing false alarms caused by small animals and making it ideal for residential settings. The 6615 model combines PIR with microwave technology, offering dual detection for enhanced accuracy and reliability in challenging environments. For high-security areas, the 6515AM and 6615AM models incorporate anti-masking features, which prevent tampering or obstruction of the sensor, ensuring continuous protection.

Mounting and design

The design of the Comfort line volumetric sensors emphasize aesthetics as well as functionality, offering white and black glossy finish variants that blend seamlessly with modern interiors. An optional bracket is available supporting wall and ceiling mount installation. The ceiling mount sensor variants provide full 360 degrees detection, ideal for open areas like lobbies, warehouses, or venues.

Performance

The Comfort line sealed optics protect against dust, bugs and other contaminants, ensuring long-term reliability in various environments. Digital signal processing filters noise and reduces false alarms, enhancing detection accuracy. The sensors spherical optics provide consistent detection coverage, minimizing blind spots across heights between 1,8 to 3,0 meters, depending the variant.

Configuration

The Comfort line includes selectable built-in EOL resistors that simplify wiring and ensure compatibility with most alarm panels. The sensor status LED indicators can be turned on or off locally or remotely, as well as its microwave and anti-mask detection controls, allowing flexibility based on security needs.

Compliance and certification

The Comfort line meets the industries EN and INCERT Grade 2 and 3 standards. Being certified, the product demonstrates its commitment to quality, safety, and regulatory compliance, providing peace of mind to installers and end-users.



Dettagli

- Sensore PIR 15m, pet friendly fino a 35 kg
- Analisi digitale del segnale
- Lente fresnel di alta qualità
- Conteggio degli impulsi
- Controllo LED di stato
- Resistenze di fine linea incorporate e selezionabili
- Finitura lucida bianca
- Certificato EN & INCERT Grado 2
- Snodo installabile a parete e a soffitto opzionale

6515PI

Sensore PIR 15m Comfort line, pet friendly

Specifiche tecniche

General

Technology	PIR
Anti masking	No
Pet immune	Yes
Detector start-up time	60 s

Detection

Max. detection range	15 m
Target speed range	0.3 to 3.0 m/s
Maximum pet weight	35 kg
Digital pulse count	1 or 2 pulses to raise an alarm

Inputs/outputs

Alarm relay characteristic	Normally closed, 100 mA at 30 VDC

Electrical

Power supply value	9 to 15 VDC, 12 VDC nominal
Current consumption	Quiescent : 15 mA Maximum : 19 mA

Physical

Physical dimensions	60 x 118 x 40 mm
Net weight	110 g
Colour	White
Housing material	2.5 mm ASA
Mounting height	2.0 to 2.2 m

Environmental

Operating temperature	−20 to +55°C
Storage temperature	−35 to +60°C
Relative humidity	95% noncondensing
Environment	Indoor
IP rating	IP30

Regulatory

EN50131 grade	Grade 2
Certification	EN50131, INCERT, SBSC

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57