# DD1012AM-D-N

## Rivelatore doppia tecnologia 12 m, 9 tende, antimascheramento VdS/EN50131 Grade 3, piroelettrico digitale

### Patented Range Gated Radar Technology

Motion sensors of the DD1000 Series incorporate a KSG Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.
The radar operates on 5.8GHz frequency and will not interfere with any WIFI networks.

The DD1012AM-D-N motion sensor incorporates a new digital pyro for an improved signal quality and a better immunity to electrical interferences.

### PIR Technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.
Within our DD1012 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.

### Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.
But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

### Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

### Anti-masking (optical and radar)

The use of Active Infrared and radar technology results in a superior anti-masking functionality that supervises the motion sensor on the inside and outside. Radar verification prevents from having unwanted AM alarms caused by e.g. insects. In advanced setting the AM alarm



### Dettagli

- La tecnologia brevettata Range Gated Radar stabilsce con precisione ill limite del campo di rilevazione del radar
- Tecnologia PIR con ottica a specchio a tende brevettata
- La versione antimascheramento utilizza la tecnologia ad Infrarossi Attivi e radar per proteggere contro tentativi di sabotaggio all'esterno e all'interno del rivelatore
- Risposta di allarme intelligente basata sulla classificazione del segnale del PIR e del radar
- Diagnostica automatica e continua su tutte le tecnologie
- Modalità ecologica: opzione per disabilitare la tecnologia radar quando il sistema di sicurezza non è inserito
- Piroelettrico digitale che rileva le fluttuazioni di temperatura con un alto grado di precisione
- In possesso di diverse approvazioni di sicurezza tra cui EN50131 Grado 3

is held until the effective source of the anti-masking (e.g. spray, tape,…) has been removed. Even partial masking – so going beyond the EN Grade III standard – will be detected when in advanced setting.

## Other members of the family

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity. The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

# DD1012AM-D-N

## Rivelatore doppia tecnologia 12 m, 9 tende, antimascheramento VdS/EN50131 Grade 3, piroelettrico digitale

## Specifiche tecniche

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Wall mount |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |
| Pry-off tamper kit | On board |
| Detector start-up time | 60 sec |

### Detection

| | |
|---|---|
| Max. detection range | 12 m |
| Detection range selection | 4, 6, 9, or 12 m selectable via dip switches |
| No. of curtains | 9 |
| Coverage (field of view) | 78° |
| Microwave frequency (nom.) | 5.8 GHz |
| Max. microwave output (at 1m) | 0.003 µW/cm² |
| Undercrawl protection | Yes |
| Target speed range | 0.1 to 4.0 m/s |
| Alarm memory | Yes |
| Alarm time | 3 s |
| Peak-to-peak ripple immunity | 2 V (at 12 VDC) |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Wired |

### Inputs/outputs

| | |
|---|---|
| Alarm relay characteristic | NC, 80 mA 30 VDC, Form A |
| Tamper relay characteristic | NC, 80 mA 30 VDC, Form A |
| Anti mask relay characteristic | NC, 80 mA 30 VDC, Form A |
| Remote control lines | Day/Night, Walk test |

### Electrical

| | |
|---|---|
| Operating voltage | 9 to 15 VDC |
| Current consumption | 10 to 22 mA (11 mA nom.) |

### Physical


| | |
|---|---|
| Physical dimensions | 126 x 63 x 50 mm |
| Net weight | 120 g |
| Colour | White |
| Mounting height | 2 to 2.6 m |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +55°C |
| Relative humidity | 95% max. noncondensing |
| Environment | Indoor |
| IP rating | IP30 |

### Regulatory

| | |
|---|---|
| EN50131 grade | Grade 3 |
| Compliancy | CE |
| Certification | EN50131 Grade 3, VdS |




In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57