SC-13-1100-0001-99

Modulo di zona incendio convenzionale wireless WZM SmartCell

Wireless Zone Monitor overview

The Wireless Zone Monitor (WZM) has been designed with flexibility in mind, allowing connection to both conventional and addressable fire alarm systems. Supporting up to 16 SmartCell wireless fire devices, communication between devices and the WZM is bidirectional and operates in the European harmonised 868 MHz frequency band.



Dettagli

- Comunicazione wireless con i dispositivi
- Veloce e semplice da installare
- Dimensioni compatte
- Display OLED 80 caratteri
- Disponibile versione a 24 Vcc
- Massimo 16 dispositivi incendio wireless

SC-13-1100-0001-99

Modulo di zona incendio convenzionale wireless WZM SmartCell

Specifiche tecniche

Electrical

Power supply type	230 VAC

Input

Input quantity	2

Physical

Colour	White
Mounting type	Surface mount

Environmental

Environment	Indoor

Regulatory

Compliancy	CE
Certification	CPR

Wireless signalling

Operating frequency	868 to 870 MHz
Output transmitter	14 dBm max. / 25 mW

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57