# FE160MS

**Eco Line magnetic lock 600 Kgf, monitored, surface mount**



## Details

- 600 Kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation

# FE160MS

## Eco Line magnetic lock 600 Kgf, monitored, surface mount

## Technische specificaties

### General

| | |
|---|---|
| Product type | Magnetic lock |

### Holding force

| | |
|---|---|
| Holding force kgf (Kilogram force) | 600 kgf |
| Holding force N (Newton) | 6000 N |

### Monitoring & status

| | |
|---|---|
| Monitored | Yes |
| LED indicator | Yes |
| Door status switch | No |
| Monitored changeover | Yes |
| Magnetic bond sensor | Yes |

### Electrical

| | |
|---|---|
| Power supply value | 12 / 24 VDC |
| Current consumption | 450 mA (+/- 2,5% @ 13,5 V) |

### Physical

| | |
|---|---|
| Physical dimensions | 266 × 73 × 40 mm |
| Colour | Aluminium |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57