DB2368IAS-W

Montagevoet, 10 cm diam., met ingebouwde isolator en slow whoop - Wit



DB2368IAS-W

Montagevoet, 10 cm diam., met ingebouwde isolator en slow whoop - Wit

Technische specificaties

Electrical

Power supply type	Loop powered

Isolation

Type	Negative line break

Physical

Colour	White
Mounting type	Ceiling mount, Wall mount
Mounting position	Ceiling, Wall
Material	High impact polycarbonate

Environmental

Vandal proof	No
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	EN54-17, EN54-3

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	DP2061N	Analoge Optische rookmelder met remote uitgang, EN54, excl montagevoet
Detection device	DP2061T	Anal. Multi-criter. Meld. Opt/therm. met remote uitgang, EN54, excl mont.voet
Detection device	DT2063N	Analoge Temperatuurmelder, met remote uitgang, EN54, excl montagevoet
Notification device	AS2368CAP-W	Rode kap voor de slowwhoop DB2368IAS-R

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57