240315

Konwencjonalny ręczny przycisk EN12094 - RĘCZNE URUCHOMIENIE

General

The 240315 is a yellow, double action manual call point used as electrical activation device in extinguishing systems for various extinguishing agents.

It is connected to the fire detection or extinguishing control panel via a conventional detector line. A red status LED optically indicates the activated condition of the device.

Construction

In comparison with plastic housings, the robust design housing made of die-cast aluminium proves advantages even after years of use thanks to its resistance to environmental impact and minimal colour fading in sunlight. Design details such as the self-closing lock cover protect the inside from dust or water penetration and facilitate easy installation and cabling. The door with the easily replaceable glass pane has an opening angle of more than 180°.

When the call point is activated, the door is mechanically prevented from closing.



UNRELEASED

Szczegóły

- Konwencjonalna technologia stosowana w większości systemów kontroli gaszenia
- Wskaźnik LED do wskazywania stanu aktywacji
- Certyfikat EN12094-3
- Instrukcje obsługi za pomocą znormalizowanych symboli typu EN54-11
- Atrakcyjna obudowa wykonana z wytrzymałego odlewu aluminiowego
- Zaprojektowany do montażu powierzchniowego
- EN standardowy przycisk typu B, podwójne działanie
- Zamontowany rezystor 100 Ohm

240315

Konwencjonalny ręczny przycisk EN12094 - RĘCZNE URUCHOMIENIE

Specyfikacja techniczna

General

Status indication	LED
Compatibility	Konwencjonalne systemy wykrywania i alarmowania
Connectivity	Linia 2-żyłowa

Electrical

Power supply type	Zone powered
Operating voltage	10 do 30 VDC
Cable specification	< 1.5 mm²
Terminals	6

Detection

Detection principle	Aktywacja ręczna
Monitoring	Off, On
Installation height	Określona przez przepisy lokalne

Output

Output quantity	1
Output type and rating	Kontakt (25 VAC @ 2A lub 60 VDC @ 2A)

Physical

Physical dimensions	127 x 127 x 35 mm (S x W x G)
Net weight	± 420 g
Colour	Yellow (RAL 1021)
Mounting type	Surface mount, Wall mount
Cable entries	Góra i dół (2 x M20×1.5), Tył (2 x 24×10 mm)
Material (body)	Die-cast aluminium
Functional marking	RĘCZNE URUCHOMIENIE

Environmental


Vandal proof	No
Relative humidity	5 do 95% bez kondensacji
Environment	Indoor
IP rating	IP43 (standard)

Regulatory

Compliancy	CE, CPR, REACH, RoHS 3, WEEE
Certification	EN12094-3
Voluntary marks	BOSEC, VdS

Wyroby zgodne

Kategoria	Odniesienie	Opis
Detection device	DM966	Wymienne przezroczyste szybki do ręcznych ostrzegaczy pożarowych



UNRELEASED

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57