DB2016

Base Standard com Isolador - Série 2000



DB2016

Base Standard com Isolador - Série 2000

Especificações técnicas

General

Addressing method	No addressing required

Electrical

Power supply type	Loop powered

Detection

Monitoring	Short circuit

Isolation

Type	Negative line break

Physical

Colour	Cloud white (RAL 9001)
Mounting type	Ceiling mount
Material (body)	Plastic

Environmental

Vandal proof	No
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	CPR

Produtos compatíveis

Categoria	Referência	Descrição
Detection device	DB2002	Base Standard 100mm - Série 2000
Detection device	DP2061N	Detetor Ótico Endereçável - Série 2000
Detection device	DP2061T	Detetor Ótico / Térmico - Série 2000
Detection device	DT2063N	Detetor Térmico Endereçável -Série 2000
Notification device	AS2368CAP-W	Tampa Branca

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57