BS127N-A

Blyackumulator 12 V, 7,2 Ah. Mått 151 x 94 x 65 mm. Till inbrottslarm/video/passerkontroll

Overview

Used for emergency exit lights, warning signs, illumination, or security systems, it can still allow uninterrupted operations for a certain amount of time in case of power is down

Application

This battery can be used for cyclic and standby applications as these have been designed to be more efficient, safer and more environmental friendly.



Detaljer

- High energy density
- Sealed leak proof construction
- Excellent performance in either float or cyclic applications
- Maintenance free
- Rechargeable lead acid battery
- Long service life

BS127N-A

Blyackumulator 12 V, 7,2 Ah. Mått 151 x 94 x 65 mm. Till inbrottslarm/video/passerkontroll

Tekniska specifikationer

General

Product type	Sealed lead acid battery

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	7.2 Ah

Physical

Colour	Black
Material	ABS

Environmental

Fire retardant	No
Vandal proof	No
Environment	Indoor

Regulatory

Compliancy	RoHS 2, WEEE
Certification	VdS

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57