ATS1473-5

ATS SmartTag (nøglebrik) blå, 5 stk.

Product Overview

Polycarbonate blue keyfob, for the ATS proximity readers. To be programmed with the ATS1621 Cardprogrammer and TITAN software. The reading distance is between 0 to 30 cm and it depends on the reader design.



Detaljer

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications

ATS1473-5

ATS SmartTag (nøglebrik) blå, 5 stk.

Tekniske specifikationer

System

Reading distance	0 to 30 cm
Custom data model	No
Supported readers	ATS Proximity Leser

Technology

Credential type	Nahdistanz
Credential operating frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Printing

Direct surface printing	No

Ordering information

Minimum order quantity	1
Cards/tags in package	5

Physical

Material	Polycarbonat
Form factor	Schlüsselanhänger
Physical dimensions	31 x 40 x 5 mm
Colour	Schwarz

Environmental

Operating temperature	-25 to +50°C
IP rating	IP67

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57