FCX-174-001

Fusion Drahtloser Multisensor-Melder

General

The FCX-174-001 multisensor detector contains an optical smoke sensor and a temperature sensor that are combined to give the final decision of a possible fire situation. The alarm response can be based on pure smoke detection, pure heat detection, or a combination of the two. Consequently the multisensor detector is suitable for a wide range of applications.

The FCX-174-001 is quick and easy to install by simply fitting to a compatible wireless base.



Einzelheiten

- Brandmeldeanzeige-LED
- Manipulationssicherer Verriegelungsmechanismus
- FastTest-Wartungsfunktion
- Von dritter Seite EN-zertifiziert
- Einfach zu installieren
- Bewährte Technologie
- Selbstüberwachung

FCX-174-001
Fusion Drahtloser Multisensor-Melder

Technische Spezifikationen

General

Status indication	LED
User interface	LED
Compatibility	Drahtlose Basis FCX-170-001, FCX-191-000, FCX-191-100 oder FCX-191-200

Electrical

Power supply type	Batterien
Cable specification	N/A

Detection

Detection principle	Photoelektrische Lichtstreuung.
Monitoring	Device type, Fault, Presence

Physical

Physical dimensions	113 x 92 mm (Ø x H) - einschließlich Sockel
Shipping weight	405 g - einschließlich Sockel
Colour	Weiß
Mounting type	Montage auf Sockel
Material (body)	Polycarbonat

Environmental

Operating temperature	-10 bis +55 °C
Storage temperature	5 bis 30 °C
Relative humidity	0 bis 95% nicht kondensierend
IP rating	IP23

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	BOSEC
Standards	EN54-5 EN54-7

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.