ATS1475X10

Set of 10x ATS1475 Proximity cards (10 x 10 cards)

Product Overview

These cards are to be used on ATS readers. The cards are unprogrammed and have the number printed for easier administration. Both the smart ship and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.



Details

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications
- Packed by 10

ATS1475X10

Set of 10x ATS1475 Proximity cards (10 x 10 cards)

Technical specifications

System

Reading distance	0 to 60 cm
Custom data model	No
Supported readers	ATS Proximity Leser

Technology

Credential type	Nahdistanz
Credential operating frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Printing

Direct surface printing	Yes

Ordering information

Minimum order quantity	1
Cards/tags in package	100

Physical

Material	PVC
Form factor	CR80 (Kredit)
Physical dimensions	86 x 54 mm
Colour	Weiß

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24