ACA-TOUCH-SLIM

Touchless slim Exit button

Product overview

The touchless exit buttons provide means to activate a request-to-exit with access control solutions without having to touch anything. This solution is achieved by using Infrared technology. Just move a hand near the front of the sensor to activate the contact. Activation is clearly indicated by an LED showing Green when active or RED when powered but not active.
Please note that direct sunlight or reflections may affect the sensitivity of the infrared sensor.



Details

- Touchless exit button using IR sensor
- Attractive, timeless design
- Adjustable distance, 3 to 15 cm
- Adjustable relay activation period
- Red and Green LED indication for standby and active
- Indoor use only

ACA-TOUCH-SLIM

Touchless slim Exit button

Technical specifications

General

Accessory group	Zutrittskontrolle
Type	Ausstiegsgerät

Electrical

Operating voltage	12 to 24 VDC
Current consumption	30 mA Idle 35 mA Active

Physical

Physical dimensions	86 x 55 x 20 mm
Net weight	43 g
Colour	Weiß
Material	ABS

Environmental

Operating temperature	-10 to +55°C
Relative humidity	95% noncondensing
Environment	Drinnen

Regulatory

Compliancy	CE
Certification	CE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 1 June 2026 - 10:59