ATS1475X10

Set of 10x ATS1475 Proximity cards (10 x 10 cards)

Product Overview

These cards are to be used on ATS readers. The cards are unprogrammed and have the number printed for easier administration. Both the smart ship and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.



Detaljer

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications
- Packed by 10

ATS1475X10

Set of 10x ATS1475 Proximity cards (10 x 10 cards)

Tekniska specifikationer

System

Custom data model	No
Supported readers	ATS Proximity Leser

Technology

Credential type	Nahdistanz
Credential operating frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Printing

Direct surface printing	Yes

Ordering information

Minimum order quantity	1
Cards/tags in package	100

Physical

Material	PVC
Form factor	CR80 (Kredit)
Colour	Weiß

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57