DDI602-F1

Outdoor, Dual Technology detector, 10.525 GHz, selectable 10/20/30 m (33/66/98 ft)



DDI602-F1

Outdoor, Dual Technology detector, 10.525 GHz, selectable 10/20/30 m (33/66/98 ft)

Spécifications techniques

General

Technology	Doppia tecnologia
Application type	Montaggio a parete
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	30 m
Detection range	30 m
Detection range selection	10, 20 or 30 m
Coverage (field of view)	70°
Microwave frequency (nom.)	10.525 GHz
Undercrawl protection	No
Alarm time	5 sek

Wired/wireless

Wired-wireless	Verdrahtet

Inputs/outputs

Alarm relay characteristic	NC / NO, Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Anti mask relay characteristic	Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Relay configuration	Vari valori EOL

Electrical

Power supply value	9 to 15 VDC
Current consumption	11 mA

Physical

Physical dimensions	147 × 187 × 140 mm
Net weight	323 g
Shipping weight	549 g
Colour	Silber
Material	Hochschlagfester ABS Kunststoff mit HDPE Abdeckung, UV stabilisiert
Mounting height	3 bis 6 m

Environmental

Operating temperature	-30 to +65°C
Environment	Draussen

Regulatory

EN50131 grade	Klasse 2
Certification	INCERT

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57