ATS1190X4

Advisor Master smard card proximity-lezers voordeelpack van 4 stuks.



ATS1190X4

Advisor Master smard card proximity-lezers voordeelpack van 4 stuks.

Technische specificaties

System

Supported card types	HiTag2
Addressing type	Indirizzamento tessere, Indirizzamento tastiere, Indirizzamento software
Reader accessory	Cover colorate opzionali

Technology

Reader type	Nærhed, Smartcard
Reader operating-transmitting frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Interface & connections

Interface	ATS RS-485, Wiegand
Connector type	Svinesvans

Inputs/outputs

Inputs	Richiesta di uscita
Outputs	1 Open Collector (25 mA)

Tamper type

Pry-off tamper	Yes

Operation

PIN keypad	No

Physical

Colour	Hvid
Material	Plastic
Mounting Type	Montaggio a superficie

Environmental

Vandal proof	No
Environment	Indendør

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57