DDI602-F1

Outdoor, Dual Technology detector, 10.525 GHz, selectable 10/20/30 m (33/66/98 ft)



DDI602-F1

Outdoor, Dual Technology detector, 10.525 GHz, selectable 10/20/30 m (33/66/98 ft)

Specyfikacja techniczna

General

Technology	Dual
Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	30 m
Microwave frequency (nom.)	10.525 GHz
Undercrawl protection	No
Alarm time	5 s

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Relay configuration	Multiple EOL values

Physical

Colour	Silver
Material	High impact ABS plastic with HDPE cover, UV stabilized
Mounting height	3 to 6 m

Environmental

Environment	Outdoor

Regulatory

EN50131 grade	Grade 2
Certification	INCERT

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57