# TVN-1204CS-4T

**TruVision NVR 12, 4 kanały, 4 porty PoE, 40 Mb/s, 4 TB**




## Szczegóły

- Konfiguracja Plug and Play
- Obsługuje kodowanie H.264, H.265 i H.265+, w zależności od kamer
- Cztery porty Plug & Play PoE (obsługa PoE-af i PoE-at) o maksymalnej rozdzielczości 4K (8MP)
- Automatyczna konfiguracja adresów IP poprzez porty Plug & Play PoE
- Przepustowość nagrywania do 40 Mb/s dla maksymalnie czterech kamer IP
- 4 TB wbudowanej pamięci masowej
- Nagrywanie w czasie rzeczywistym, do 4 MP
- Wyjście monitora HDMI/VGA
- Automatyczne wykrywanie kamery IP TruVision
- Import/eksport konfiguracji kamery IP
- Obsługa UltraSync dla zdalnego dostępu bez przekierowania portów
- Wykrywanie ruchu, VCA, maskowanie prywatności i wykrywanie sabotażu, zależne od wykorzystanych kamer
- Dedykowane wykrywanie osób/pojazdów w połączeniu z obsługiwanymi kamerami
- Obsługa kamer innych firm za pośrednictwem ONVIF Profile S lub RTSP (protokoły niestandardowe)
- Integracja z centralami SSWiN Aritech IP poprzez raportowanie SIA/XSIA
- Obsługa klawiatury IP TVK-600
- Obsługa nagrywarki DVD USB
- Pełny dostęp przez przeglądarkę, menu ekranowe OSD oraz oprogramowanie do podglądu na żywo, nagrań i konfiguracji
- Aplikacja TVRMobile na iOS i Android do zdalnego podglądu
- Obsługa TruVision Navigator

- Integracja zewnętrzna przez SDK

## Reasons to choose TVN 12

The TVN 12cS recorder series offers a full-featured, compact recording solution for IP cameras with a maximum resolution of 8 MP(4K).
The TVN-1204cS is a cost-effective, easy-to-use recorder capable of recording up to four IP cameras, connected to the built-in PoE ports or via the LAN network.

## Easy to use

A setup wizard with auto detection of IP cameras guarantees a fast installation of the recorder.
The TVN 12cS can be added to the internet without port forwarding or VPN, thanks to the built-in UltraSync connectivity. Showing remote video on mobile applications was never easier.
In combination with dedicated TruVision cameras that can support people and/or vehicle detection, the TVN 12 recorder series can find relevant events faster and without efforts.

## Applications

The TVN 12cS is the ideal recording solution for small commercial and residential applications, where ease of use and fast deployment time are important.

# TVN-1204CS-4T

## TruVision NVR 12, 4 kanały, 4 porty PoE, 40 Mb/s, 4 TB

## Specyfikacja techniczna

### General

| | |
|---|---|
| Technology | IP |
| Operating system | Embedded Linux |
| Rack mountable | No |

### Video/audio input

| | |
|---|---|
| Camera channels | 4 |
| IP camera channels | 4 |
| Camera bandwidth | 40 Mbps |
| Audio compression | G.711alaw, G.711ulaw, G.722, G.726 |
| Max. IP audio in | 4 |
| Max. analog audio In | 1 |
| Supported video compression standards | H.264, H.265, H.265+ |
| Supported video streaming standards | Onvif, RTSP Custom Protocols |

### Local viewing

| | |
|---|---|
| HDMI output | 1 |
| HDMI version | 1.4, 2.0 |
| VGA output | 1 |
| Max. local output resolution | 4K |
| Synchronous playback OSD (channels) | Do 4 kanałów (1080P) |

### Remote viewing

| | |
|---|---|
| Total available viewing bandwidth | 80 Mbps |
| Max. live viewing streams | 128 strumieni |
| Max. playback viewing streams | 8 strumieni |
| Max. simultaneous playback web browser | Do 8 kanałów |
| Reverse playback web browser (channels) | Do 8 kanałów |
| UltraSync support | Yes, embedded |
| Software compatibility | Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile |
| Browser compatibility | Google Chrome, Internet Explorer, Mozilla Firefox, Safari |

### Storage

| | |
|---|---|
| Storage capacity | 4 TB |
| SATA interfaces | 1 |
| Max. capacity per SATA HDD (TB) | 8 |
| Maximum recording resolution | 4 K |
| Recording modes | Continuous, Event, Manual |
| External storage | NAS |
| Edge failover recording | Yes |

### Networking

| | |
|---|---|
| Network interface cards (NIC) | 1 |
| NIC type | RJ-45 10/100 Mbps self-adaptive Ethernet interface |
| PoE ports | 4 |
| Total PoE budget | 50 W |
| PoE standards supported | PoE-af, PoE-at |
| Max. PoE budget per port | ≤30 W |
| Plug & Play PoE support | Yes |
| Flexible PoE allocation | Yes |
| DNS support | DDNS, ezDDNS, No-IP |
| HTTPS support | Yes |

### External interfaces

| | |
|---|---|
| USB interface back | 1 |
| USB interface front | 1 |
| Alarm inputs | 4 |
| Alarm outputs | 1 |
| Max. analog audio outputs | 1 |

### Electrical

| | |
|---|---|
| Operating voltage | 48 VDC |
| Power supply type | 48 VDC |
| Power consumption without HDD (W) | ≤65 W |

### Physical

| | |
|---|---|
| Physical dimensions | 320 x 240 x 48 mm (W x D x H) |
| Net weight | 1.2 kg |
| Colour | Black |

### Environmental

| | |
|---|---|
| Operating temperature | -10 do +55°C |
| Relative humidity | 10 do 90% bez kondensacji |

### Regulatory

| | |
|---|---|
| Compliancy | CE, FCC, RCM, REACH, RoHS, UKCA, UL, WEEE |

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 20:20