DM2080I-N

2000 Series Addressable Manual Call Point with Isolator - RED



Details

- Type B (double action) manual call point
- Includes dual isolator
- Complies to DIN14655
- RED (alarm) and YELLOW (Isolated) LEDs

DM2080I-N

2000 Series Addressable Manual Call Point with Isolator - RED

Technische specificaties

General

Addressing method	Dip-Schalter

Electrical

Power supply type	Lus aangedreven

Detection

Monitoring	Device type, Presence

Isolation

Type	Negativer Zeilenumbruch

Physical

Colour	Rood (RAL 3001)
Mounting type	Vægmontering
Material (body)	RA6 + 30%gF

Environmental

Vandal proof	No
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	CPR

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	DM966	Replacement CLEAR Windows for Push-button-activated Manual Call Points

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57