DM2080I-N

Manuell brandlarmknapp, adresserbar, röd

General

The DM2080I-N is an addressable, 2000 series RED manual call point with dual isolator included. Its double action push button has a latching mechanism and is designed according to DIN14655 standards. It is supplied in a in a durable plastic housing with alarm indication LED and has a door opening angle of more than 180° for ease of access.

Installation

The DM2080 is made ready for installation on German junction boxes. The enclosure has an IP rating of DIN IP42 and boasts generous space for the wiring. A t-insulator separates the outside from the inside, and a connector for screened cable in the connection area is available. A yellow LED is available internally to indicate the status for the isolator.

Approval

The DM2080I-N is VdS approved: G 203056



Detaljer

- Type B (double action) manual call point
- Includes dual isolator
- Complies to DIN14655
- RED (alarm) and YELLOW (Isolated) LEDs
- VdS Approved

DM2080I-N

Manuell brandlarmknapp, adresserbar, röd

Tekniska specifikationer

General

Addressing method	DIP Switches

Electrical

Power supply type	Lus aangedreven

Detection

Monitoring	Device type, Presence

Isolation

Type	Negative line break

Physical

Colour	Rood (RAL 3001)
Mounting type	Vægmontering
Material (body)	RA6 + 30%gF

Environmental

Vandal proof	No
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	CPR

Kompatibla produkter

Kategori	Referens	Beskrivning
Detection device	DM966	Replacement Clear Windows For Push-Button-Activated Manual Call Points

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57