ATS1110A-N

Advisor Advanced betjeningspanel 2x16 karakter LCD

Remote Arming Stations

The ATS1110A is part of the Remote Arming Station family for the Advisor Advanced security system. The RAS family consists of a range of keypads and card readers which can be used in different environments, in and out-door. The ATS1110A can be used for configuration and management of the system, as well as for opening doors and arming/disarming areas. In an easy way, the ATS1110A gives a status overview from your security system with both visual and audio indicators.

Product Overview

The ATS1110A is a modern ergonomic design and has a clearly readable text on a 2 x 16 characters LCD for displaying system programming, alarm and access control functions. The viewing angle of the display is adjustable via the keypad as well as the volume level of the built-in buzzer. Four arrow keys will navigate the user easily through the programming and operational features and 6 additional functions key will complete this user-friendly interface.

Indications

Four status LED's will continuously update the user on mains condition, faults, access control and alarms.
Green - Power LED is on when the control panel is powered by the AC supply.
Yellow - Fault LED illuminates to indicate detection of a system fault.
Blue - Access LED flashes when access to an area assigned to the RAS is granted.
Red - Alarm LED illuminates when there is a system tamper or an area assigned to the RAS is in alarm state.
The Arming Station can display the status of 16 areas using 16 LED's on the front, while the LCD shows details of alarms or a pre-programmed text.
The area may be identified by viewing the 16 area LEDs visible when the RAS cover is open or removed and the indications are as follows:
• The LED illuminates when its corresponding area is armed.
• The LED flashes slowly when a fault is detected.
• The LED flashes quickly when an alarm occurs.

Mounting

The RAS cover is hinged at the bottom. To open, grasp the cover at the sides or the top and pull gently — the cover will swing down on its pins. The cover may be fully removed by gently prising one of the pins away from the body of the RAS and pulling. The metal mounting plate at the rear is held by a locking screw.



Detaljer

- 2 x 16 characters LCD
- User adjustable buzzer
- User adjustable LCD contrast
- 16 Area indication
- Door release indication

ATS1110A-N

Advisor Advanced betjeningspanel 2x16 karakter LCD

Tekniske specifikationer

General

User interface	2 x 16 Char LCD, Touch Buttons
Product line	Advisor Advanced
Status LEDs	16

System

Function keys	4
Addressing type	Mikroprzełączniki
Supported cable type	WCAT 52/54 or equivalent

Communication

Communication type	Kablede

Inputs/Outputs

Inputs	1
Input type	Request to Exit
Outputs	1
Output type	Open collector, 50 mA Max

Electrical

Operating voltage	9 to 14 VDC
Current consumption	26 mA typical 95 mA max

Physical

Physical dimensions	92 x 165 x 25 mm
Net weight	296 gr
Colour	Hvid
Form factor	Lodret
Cover	Obudowa odchylana
Mounting type	Montaż nawierzchniowy

Environmental

Operating temperature	0 to +50°C
Relative humidity	95% non condensing
Environment	Indendør
IP rating	30

Regulatory

EN50131 grade	Lønklasse 3
Compliancy	CE, RoHS
Certification	VdS

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57