# ACT430E-5

## (5 stk.) Mifare Classic S50 proxbrik med 7-byte UID (CSN)

### Product overview

These Mifare Classic 1k keyfobs are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other KGS Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



### Detaljer

- Read only for CSN (7-byte)
- Read / Write function for card sectors

# ACT430E-5

## (5 stk.) Mifare Classic S50 proxbrik med 7-byte UID (CSN)

## Tekniske specifikationer

### System

| | |
|---|---|
| Reading distance | 0 to 10 cm |
| Memory size | 1 kB |
| No. of Mifare bytes CSN | 7 bajtów (S50) |
| Supported readers | Czytniki ACI406/407 Mifare, Czytniki ATS1160/1161 Mifare |

### Technology

| | |
|---|---|
| Credential type | Nærhed |
| Credential operating frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN) |

### Ordering information

| | |
|---|---|
| Cards/tags in package | 1 |

### Physical

| | |
|---|---|
| Material | PA6 |
| Form factor | Brelok |
| Physical dimensions | 45 x 30 x 14 mm |
| Net weight | 16 g |
| Colour | Sort |

### Environmental

| | |
|---|---|
| IP rating | IP66 |

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57