DDI602-F2

Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)



DDI602-F2

Outdoor, Dual Technology detector, 10.587 GHz, selectable 10/20/30 m (33/66/98 ft)

Technische Spezifikationen

General

Technology	Dualna
Application type	Uchwyt ścienny
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	30 m
Microwave frequency (nom.)	10.587 GHz
Undercrawl protection	No
Alarm time	5 sek

Wired/wireless

Wired-wireless	Verdrahtet

Inputs/outputs

Relay configuration	Wiele wartości EOL

Physical

Colour	Silber
Material	Hochschlagfester ABS Kunststoff mit HDPE Abdeckung, UV stabilisiert
Mounting height	3 do 6 m

Environmental

Environment	Draussen

Regulatory

Certification	INCERT

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.