# AS508

## Outdoor siren with single amber beacon and inner metal shield



## Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Metal Inner cover
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Fully compliant with CE, BS and IS requirements
- Self detection of cable cutting or tampering
- Installer Friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

# AS508

## Outdoor siren with single amber beacon and inner metal shield

## Technical specifications

### General

| | |
|---|---|
| Accessory group | Sirene |
| Type | Udendørs sirene |
| Sounder output (dB @ distance) | 114 dB at 1 m (typical) |

### Flash specifications

| | |
|---|---|
| Flash frequency | 50 to 60 flashes/min |

### Electrical

| | |
|---|---|
| Operating voltage | 10 to 14.5 VDC |
| Current consumption | 350 mA<br>40 mA (standby, with NiCd battery)<br>20 mA (standby, without battery) |

### Physical

| | |
|---|---|
| Physical dimensions | 210 x 300 x 55 mm |
| Net weight | 1235 g |
| Material | ABS |
| Material | ABS (3 mm) |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to 55°C |
| IP rating | IP54 |

### Sounder

| | |
|---|---|
| | Double piezo |

### PCB protection

| | |
|---|---|
| | Fully potted |

### Tamper & pry-off

| | |
|---|---|
| | Yes |

### Frequency

| | |
|---|---|
| | 0.5 to 3 kHz |

### Cut-off timer

| | |
|---|---|
| | 3, 5, 10, 20 min |

### Comfort LED

| | |
|---|---|
| | Yes |

### Low voltage detection

| | |
|---|---|
| | Yes |

### Metal inner cover

| | |
|---|---|
| | Included |

### Optional self-activating battery

| | |
|---|---|
| | 10.8 V / 280 mAh |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 May 2026 - 17:12