TVM-2414

TruVision 24" LED, VGA, HDMI, audio speaker, stereo audio In, Full HD, 1920 x 1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI or VGA connections, these monitors are a great fit for today's demanding video surveillance market.
Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.



Capabilities

The TVM-2414 is a 24" class monitor, offering HDMI and VGA connections. The monitor is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.

Detalles

- 24" LED Backlight
- Full HD resolution
- Ultra-thin body with ultra-thin border for 3 sides
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 4000:1 contrast ratio for crisp images
- Multiple inputs including VGA, HDMI

TVM-2414

TruVision 24" LED, VGA, HDMI, audio speaker, stereo audio In, Full HD, 1920 x 1080

Especificaciones técnicas

General

Technology	LED
VESA compatibility	100 x 100 mm
Included accessories	Podręcznik, Kabel zasilający
Bezel width	1.8 mm (top/left/right), 21.4 mm (bottom)

Display

Screen size	23.8”
Aspect ratio	16:9
Contrast ratio	4000:1
Pixel pitch	0.2745 (H) × 0.2745 (V) mm
Viewing angle (H/V)	178° / 178°
Response time	6.5 ms (typ) (G to G) OD 5 ms
Brightness	250 cd/m² (Typ)
Recommended resolution	1920 x 1080 @ 60 HZ
Backlight	E-LED
Color depth	8 bit
Active display area	527.04 (H) × 296.46 mm (V)
Haze	Anti-Glare, 3H (Without Haze)

Interface

BNC video I/O	Nie
VGA video in	Yes
HDMI video in	1
PC stereo in	Yes
Audio out	No

Operations

Controls	Power, Up/Down, Left/Right, Source, OSD Menu
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish
Remote control support	No

Electrical

Power supply type	100 bis 240 VAC
Power consumption	<25 W
Standby power consumption	≤ 0.5 W
Power supply	DC 12 V, 2.5 A

Physical

Physical dimensions	538 × 326 × 37 (without stand) 538 × 407 × 186 (with stand)
Net weight	2.63 kg
Shipping weight	3.34 kg
Colour	Schwarz
Housing Type	Plastik

Environmental

Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Relative humidity	20 to 90% noncondensing
Environment	Drinnen

Regulatory

Compliancy	CE, UKCA

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 20:20