ACT430E-5

(5-pack) Mifare Classic S50 with 7-byte UID (CSN) Keyfob

Product overview

These Mifare Classic 1k keyfobs are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other KGS Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



Dettagli

- Read only for CSN (7-byte)
- Read / Write function for card sectors

ACT430E-5

(5-pack) Mifare Classic S50 with 7-byte UID (CSN) Keyfob

Specifiche tecniche

System

Reading distance	0 to 10 cm
Memory size	1K
No. of Mifare bytes CSN	7 Byte (S50)
Supported readers	Leitores Mifare ACI406/407, Leitores Mifare ATS1160/1161

Technology

Credential type	Nærhed
Credential operating frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN)

Ordering information

Cards/tags in package	1

Physical

Material	PA6
Form factor	Comando
Physical dimensions	45 x 30 x 14 mm
Net weight	16 g
Colour	Sort

Environmental

IP rating	IP66

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57