DM966

Replacement clear windows for push-button activated manual call points

General

The DM966 is a replacement CLEAR window without the normally printed, semi-circle emphasizing the push button. It is used for the push-button-activated manual call points in the series DM860, DM880, DM950 and DM2080.



Details

- Clear glass without inscriptions
- Easy replacement

DM966

Replacement clear windows for push-button activated manual call points

Technical specifications

General

Compatibility	2403xx, DM800, DM950 & DM2080 series manual call points

Physical

Physical dimensions	80 x 80 x 0.9 mm (W x H x D)
Colour	Genomskinlig
Mounting type	Infoga
Material (body)	Glas
Functional marking	No marking

Environmental

Vandal proof	No
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE

Compatible products

Category	Reference	Description
Detection device	240315	Conventional EN12094 manual call point, Manual Release
Detection device	240320	Conventional DIN manual call point, Hausalarm
Detection device	240335	Conventional DIN manual call point, Feuer
Detection device	240345	Conventional EN12094 manual call point, Emergency Stop
Detection device	240365	Conventional manual call point, Abort
Detection device	DM880B	880 Series Push-Button-Activated Manual Call Point In Plastic Housing (Blue)
Detection device	DM980BI-N	950 Series Manual Call Point With Isolator - Blue - Plastic Housing
Detection device	DM980I-N	950 Series Manual Call Point With Isolator - Red - Plastic Housing

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 April 2025 - 9:13