# DT2063N

**2000 Series addressable heat detector with dual alarm LEDs and a remote indicator output**



# DT2063N

## 2000 Series addressable heat detector with dual alarm LEDs and a remote indicator output

## Technische specificaties

### General

| | |
|---|---|
| Addressing method | Rotary switch |

### Electrical

| | |
|---|---|
| Power supply type | Slingdriven |

### Detection

| | |
|---|---|
| Monitoring | Alarm threshold |
| Alarm temperature (typical) | > +40°C |

### Physical

| | |
|---|---|
| Colour | Wolkenweiß (RAL 9001) |
| Mounting type | Loftmontering |
| Material (body) | Plastic |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Application temperature (typical) | +25°C |
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CPR |

### Compatibele producten

| Categorie | Referentie | Beschrijving |
|---|---|---|
| Detection device | DB2002 | Montagevoet 10 cm - 4 connectoren |
| Detection device | DB2004 | 2000 Series Detector Deep Base, 5 Terminals |
| Detection device | DB2016 | Isolator Montagevoet 10 cm - 2 connectoren |
| Notification device | AI672 | Optische alarm indicator |
| Notification device | AI673 | Optische en akoestische nevenindicator |
| Notification device | DB2368IAS-W | 2000 Series Base Sounder with Isolator - WHITE |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57